

AVAILABLE  
60lb CAPACITY  
AC-4000ic



### Specifications

**Capacity (Dual Range):**

15 lb x 0.005 lb/30 lb x 0.01 lb

**Capacity (Single Range):**

30 lb x 0.01 lb

30 lb x 0.01 lb/60 lb x 0.02 lb (AC-4000ic)

**Display Items:**

Tare: Four-digits  
Unit price: Five-digits  
Weight: Five-digits  
Total Price: Six-digits

**Display:**

Fluorescent display (Upper)  
Dot matrix display (Lower) (256 x 16 dots)

**Printing Speed:**

3.2 in (80 mm) per second

**Preset Keys:**

92 one-touch preset keys  
184 preset keys (Assign two items per key)

**Memory Capacity:**

2 MB

**Label:**

Width: 1.5 in - 2.5 in (38 mm - 64 mm)  
Length: 1.2 in - 9.5 in (30 mm - 240 mm)

**Label Roll:**

Inside diameter: 1.6 in (40 mm)  
Outside diameter: 3.9 in (100 mm)

**Communication:**

Static TCP/IP 10/100 Base T Ethernet

**Weight:**

24 lbs

**Power Supply:**

AC100V/120V/220V/240V, 50/60 Hz

**Power Consumption:**

Stand-by 50W, In operation 100W

**Classification:**

NTEP CC 95-057A6, UL listed

**Warranty:**

One-year limited warranty

## Ishida AC-4000/B/ic

Price Computing Scale/Printer

Networking capabilities along with user-friendly operation make the AC-4000 series an ideal supermarket scale for bakeries, delis, seafood, meat and produce applications. The AC-4000 communicates via standard Ethernet or optional wireless transmission and allows quick label changes with front-loading cassettes. Choose from multiple label formats and use the powerful batch printing feature for increased productivity.

### Standard Features

- Dual-range weighing (0-15 lb x 0.005 lb/15-30 lb x 0.01 lb)
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Bright VFD dot matrix display for alphanumeric messaging
- 184 function keys assist with intuitive operation
- Fast printing speed results in greater customer throughput
- Multiple label formats for multi-department support
- Powerful batch printing feature frees operator's time
- Flash ROM for remote update of application software
- Proportional tare
- Prints all legally required nutrition, safe handling, ingredient and country of origin information
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

### AC-4000/ic with Label Cassette

PART #	MODEL	CAPACITY
80808	AC-4000	15 lb x 0.005 lb/30 lb x 0.01 lb
96897*	AC-4000 with RF	15 lb x 0.005 lb/30 lb x 0.01 lb
96931	AC-4000ic	30 lb x 0.01 lb/60 lb x 0.02 lb
Consult*	AC-4000ic with RF	30 lb x 0.01 lb/60 lb x 0.02 lb
AC-4000B NON-LABEL CASSETTE		
79477	AC-4000	15 lb x 0.005 lb/30 lb x 0.01 lb
96898*	AC-4000 with RF	15 lb x 0.005 lb/30 lb x 0.01 lb
96932	AC-4000ic	30 lb x 0.01 lb/60 lb x 0.02 lb
Consult*	AC-4000ic with RF	30 lb x 0.01 lb/60 lb x 0.02 lb

\*RF is factory installed (includes part no. 92462).

\*\*License file required for operation. Must supply store name and address at time of order. One license required per location. Symbol® is a registered trademark of Motorola Technologies, Inc.



Label cassette, AC-4000

AC-4000i pictured with optional remote scale base. See page LW-34 in this catalog for ordering information and wrap station options.