



AC-4000D pictured with optional wrap station components.

## Ishida AC-4000D

Price Computing Scale/Printer/Console

Networking capabilities combined with user-friendly operation, make the AC-4000D an ideal supermarket prep scale system for deli, seafood, meat and produce applications.

AC-4000D communicates via standard Ethernet or optional internal wireless communication. The modular components fit any handwrap station.

The bright, alphanumeric display provides valuable operator information including price, weight, tare and description. Multiple label formats, quick weighing and fast printing speed increase pre-pack productivity.

### Standard Features

- Dual-range weighing (0-15 lb x 0.005 lb/15-30 lb x 0.01 lb)
- Flexible configuration for ergonomic operation
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Flash ROM for remote update of application software
- Increased productivity with large 9 inch label rolls
- Bright dot matrix display for alphanumeric messaging
- 184 function keys assist with intuitive operation
- System includes scale, keyboard/display, and printer
- Prints all legally required nutrition, safe handling, ingredient and country of origin information
- Stainless steel enclosure suitable for USDA applications
- Powerful batch printing feature frees operator's time
- Proportional tare
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

### AC-4000D

PART #	MODEL	CAPACITY
80316	AC-4000D	15 lb x 0.005 lb/30 lb x 0.01 lb
96899*	AC-4000D with RF	15 lb x 0.005 lb/30 lb x 0.01 lb

Please refer to the Labels section of this catalog for ordering information and case quantity pricing.



### Specifications

**Capacity (Dual-Range):**

15 lb x 0.005 lb/30 lb x 0.01 lb

**Capacity (Single-Range):**

30 lb x 0.01 lb

**Display Items:**

Tare: Four-digits  
Unit price: Five-digits  
Weight: Five-digits  
Total: Six-digits

**Display:**

Fluorescent display (Upper)  
Dot matrix display (Lower) (256 x 16 dots)

**Printing Speed:**

3.2 in (80 mm) per second

**Preset Keys:**

92 one-touch preset keys  
184 preset keys (Assign two items per key)

**Memory Capacity:**

2MB

**Communication:**

Static TCP/IP Ethernet 10/100 base T

**Label Roll:**

Inside diameter: 3.0 in (76 mm) min  
Outside diameter: 9.0 in (230 mm) max

**Weight:**

47 lb

**Power Supply:**

AC100V/120V/220V/240V, 50/60Hz

**Power Consumption:**

Standby: 50W  
Operation: 100W

**Classification:**

NTEP CC 95-057A6  
UL listed

**Warranty:**

One-year limited warranty