



BC-4000L2i pictured with remote scale base and optional wrap station components.



Specifications

Weighing Resolution:

3,000 display divisions maximum

Remote Scale Base Capacity:

15 x 0.005 lb/30 x 0.01 lb (Dual-range)
30 x 0.01 lb (Single-range)

Display:

LCD, backlit, alphanumeric: BC-4000L2i
LED, red, numeric: BC-4000Ei

Display Items:

Tare: Four-digits
Unit price: Five-digits
Weight: Five-digits
Total price: Six-digits

Preset Keys:

84 one-touch preset keys
168 presets (Assign two items per key)

Platter (Inactive):

14.0in x 9.2in

Memory Capacity:

2MB

Communication:

Static TCP/IP 10/100 Base T Ethernet

Printing Speed:

3.2in (80mm) per second

Label:

Width: 1.5in - 2.5in (38mm - 64mm)
Length: 1.2in - 9.4in (30mm - 240mm)

Label Roll:

Inside diameter: 1.6in (40mm) min
Outside diameter: 3.9in (100mm) max

Label Backing Paper:

Width: Up to 2.6in (66mm)

Weight:

Indicator: 21 lb
Base: 27 lb

Power Supply:

AC100V/120V/220V/240V, 50/60Hz

Power Consumption:

Stand-by 50W
In operation 100W

Classification:

NTEP CC 07-005
UL listed

Warranty:

One-year limited warranty

Ishida BC-4000L2i/Ei

Price Computing Printer/Remote Scale Base

Networking capabilities and user-friendly operation make the BC-4000 with remote scale base systems ideal for prepack operations.

This series has two display types at various price points. Choose from multiple label formats for increased productivity and versatility. With standard Ethernet or optional wireless connectivity, the BC-4000 offers extraordinary power at an exceptional value.

Standard Features


- Dual-range weighing (0-15 x 0.005 lb/15-30 x 0.01 lb)
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Up to 168 function keys assist with intuitive operation
- Fast printing speed results in greater customer throughput
- Multiple label formats for multi-department support
- Powerful batch printing feature frees operator's time
- Flash ROM for remote update of application software
- Proportional tare
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale
- Convenient side-loading label feature

BC-4000L2i/Ei

PART #	MODEL	CAPACITY
101343	BC-4000L2i, LCD display	Scale base sold separately
101345	BC-4000Ei, LED display	Scale base sold separately
REMOTE SCALE BASE, STAINLESS STEEL		
99321	12.0in x 18.0in x 4.0in	15 lb x 0.005 lb/30 lb x 0.01 lb

Please refer to the Labels section of this catalog for ordering information and case quantity pricing.

BC-4000 SERIES DISPLAYS



LCD, backlit alphanumeric: BC-4000L2



LED, red, numeric: BC-4000E