Ishida IL-EMZ
Large Capacity Label Printer with Color Touchscreen

Printing speeds of 100 mm per second and unique batching capabilities give the IL-EMZ an edge in high volume applications. Its front loading feature and large 9 inch label roll capacity keep you up and running longer. The ability to print custom graphics produces eye-catching labels with all required nutritional and ingredient information.

Designed to enhance productivity, a fully customizable color touchscreen provides easy access to PLUs via category keys. Networking capability with ScaleLink Pro and other third-party product management software helps maintain consistent and accurate pricing.

From ergonomic design to high-speed printing, the IL-EMZ offers the latest technology to streamline prepackaging operations.

Standard Features

- Large color touchscreen with adjustable viewing angle
- Front-loading, 9 in (230 mm) label roll capacity
- 3 in thermal head
- Prints all legally required ingredient and nutritional information
- Stores and prints graphics for custom labeling
- Ethernet communications

- Up to 99 pages of speed keys
- Assign images to category, presets, or function keys
- 21 tactile keys
- 34 MB of memory
- 30+ selectable fixed bar code formats
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

IL-EMZ

PART #	MODEL	CAPACITY
100811	IL-EMZ, large capacity label printer with color touchscreen	No scale base

Please refer to the labels section of this catalog for ordering information and case quantity pricing.

Specifications

Display:
10.4 in color liquid crystal VGA with backlight, 640 x 480 dots

Display Items:
Unit price: Five-digits
Total price: Six-digits
Photo images for categories, presets and function keys

Label Size:
Width: 1.5 - 3.1 in (38 - 80 mm)
Length: 1.2 - 7.9 in (30 - 200 mm)

Preset Keys:
3960: 40 x 99 pages

Label Roll:
Inside diameter: 3.0 in (76 mm) min
Outside diameter: 9.0 in (230 mm) max

Memory Capacity:
34 MB

Label Backing Paper:
Width: up to 3.3 in (84 mm)

Communications:
Static TCP/IP 10/100 Base T Ethernet

Operating Conditions:
Temperature: 32°F-104°F (0°C - 40°C)
Humidity: 20 - 85% (no condensation)

Interface:
Two PCMCIA slots

Power Supply:
AC110 to 120V, 60Hz, 4A

Print Head:
3 in (76mm), direct thermal

Power Consumption:
Stand-by: 50W
In operation: 120W

Print Speed:
4 in (100mm) per second

Weight:
41.8 lb (19.0 kg)

Classification:
CSA 1968136

Warranty:
One-year limited warranty